

TELEINDUSTRIA srl

phone:	+39 02 45713729
email:	sales@teleindustria.it
website:	www.teleindustria.com

INDUSTRIAL TELEPHONE SYSTEM Full-ip server Desqo™Mini

DESQO™













LICENSES FREE

DESQO™ does not require any expiring software license. One time the platform is purchased all software features are guaranteed, with no limit of time. Special purchasing tariff is applied when using TELEINDUSTRIA'S VoIP telephones, but the platform is open to any Sip based telephone.

SIZING of the HARDWARE

DESQO™ can be equipped with external modules for FXS ports for analogue users and with FXO ports for connection to the PSTN network.

INTELLIGIBILITY INDEX

The **DESQO™** system combined with the entire gamma of **TELEINDUSTRIA™** service and emergency communication terminals guarantee a high level of conversation quality and an intelligibility index that complies with the most stringent requirements of the regulations in force.

REFERENCE RULES and STANDARDS

EN 60820; EN 62368-1; EN61000-6-2:2019; EN61000-6-3:2021; EN 50121-4 EN60945;

ORDER CODES

DSQ-50:.....SIP server

TELEPHONE PLATFORM DESOO™Mini

DESQO™Mini is a VoIP platform designed to generate private **professional telephone systems**.

The platform is entirely based on **free and internationally widespread protocols**, so it can accept virtually any kind of telephone equipment that meets international SIP standards.

The **DESQO™** platform offers the possibility of obtaining **fully redundant hardware**, an almost indispensable function in the aforementioned contexts.

DESQO™ supports all the functions generally required in professional industrial and emergency telephone systems, not present in common VoIP-SIP servers intended for civil communications.

OPTIONAL FUNCTIONS

- Multiple consoles in Control Room
- Audio recording of conversations
- SCADA interface
- SNMP query

PhoneMap™ - Graphical maps

The **PhoneMap™** option allows the display of a graphical map with the icons of the individual SOS telephones and the status of each SOS station.

TelDia™ - Remote Inquiry

The **TelDia™** option allows automatic monitoring of TELEINDUSTRIA™ SOS telephones, with detection of the good functioning status and the fault status.

Voice Recorder

The **VoiceRec™** option allows the audio recording of emergency conversations, listening to the recordings and exporting the related audio files in wav format.

Basic configuration

The basic server DSQ-50 offers limited functions and is generally used for small size systems.



TELEINDUSTRIA srl

INDUSTRIAL TELEPHONE SYSTEM Full-ip server Desqo™Mini

SPECIFICATIONS

GENERAL 117.02.40
Dimensions:
Weight:
Power:
Mounting:
Temperature Range:0°C ÷ +50°C
Relative Humidity:
HARDWARE
Processor: INTEL ATOM
Storage:
Memory:
16.16.7
CAPACITY
Subscribers' capacity
Busy Hour Call:
IP Phones:
Analog Phones:up to 16 FXS user ports with external Gateways
NETWORK FEATURES
IP Priority:
IP Security:
SIP:
VoIP Internal Networking:
VoIP External Networking:
SIP Trunk:available
Analog Trunk:
GSM Trunk: external Gateway
Configuration: web
Monitoring & Logging:SNMP trap, SNMP MIB, Syslog, Web, email, SqLite
SW Upgrade: web system recovery upgrade
VoIP Audio:
Conference:available, 25 channels, no limits to participants
Group Call:
Call Modes:
Audio Messaging:
ENHANCED EMERGENCY FUNCTIONS
Telephones Monitoring:
Audio Recording: Recording of conversations Icons and Graphic Map: Dynamic configurable map with state icons of subscribers
Dynamic Configurable map with state icons of subscribers
STANDARDS
EU Compliance: European Directives 2014/35/UE; 2014/53/EU
EN standards :
Liv Standards :

Not all the above features and functions are available on all $\mathsf{DESQO^{TM}}$ configurations. At purchasing phase, please agree with the local agency/dealer the features you need.