

**TELEINDUSTRIA srl**

phone: ..... +39 02 45713729

email: ..... sales@teleindustria.it

website: ..... [www.teleindustria.com](http://www.teleindustria.com)

# Emergency & Hot-Line VoIP (SIP) PoE vandal resistant & weatherproof IP66 Industrial Telephone with door aluminum body and handset TEL700M0-Sip

## ERCOTEL-ip®



### AVAILABLE COLORS

YELLOW RAL1023	GREY RAL7030	BLACK RAL9005	RED RAL3020	ORANGE RAL2003
-------------------	-----------------	------------------	----------------	-------------------

Protection index [EN 60529]	IP66
Impact Resistance [EN 62262]	IK10
Operating temperature:	-40°C ÷ +70°C
MTBF:	250.000 hours
MTRR:	3 minutes
Handset & Body materials:	aluminium + stainless steel
Colour of handset:	Grey, Black or Red
Hook:	magnetic
Handset's cord:	stainless-steel flexible, 200kg resistance
Bell:	95dB @ 1 m (with door closed or open)
Dimensions:	364 x 257 x 175 mm
Weight:	5,85 kg

### ORDER CODES

TEL700M0-Sip: ..... Without keypad (Hot-Line & Autodialing)  
TEL700M3-Sip: ..... 3 buttons (Autodialing)

The **ERCOTEL-ip® TEL700-Sip** is probably the more performing and innovative **Emergency & Hot-Line Telephone** on the worldwide market. It is totally made of aluminum and INOX stainless-steel. The door is there to keep it clean, not for protecting against water and dust. In fact it is weather-proof **IP66 & IK10** also when the door is open.

### MAIN CHARACTERISTICS

Equipped with the native VoIP electronic card XCS-182 release 2022-1, HD Voice, DESQO™ ready.  
Protocol: ..... SIP  
Power: ..... PoE or 12Vdc  
SIP Servers: ..... up to 3 SIP servers  
Electronic Bell: ..... up to 95dB@1m, adjustable  
Hook: ..... magnetic, high protection  
Programmable: ..... webpage

### RINGING WITH CLOSED DOOR

The integrated electronic ringing bell **95dB at 1 meter** is still operating without attenuation **when the door is closed**.

### AFD – AUTOMATIC FAULT DETECTION

The telephone supports the **automatic fault detection**, including the audio test of microphone and earpiece. A Blue LED is permanently flashing to show the correct operability of the telephone. Ready for remote diagnostic software TelDia™.

### WITHOUT KEYPAD

The **ERCOTEL-ip® TEL700M0-Sip** has no keypad. It is commonly used for **Hot-Line service** by activating the function on your i-PBX, or it can start an autodialing when lifting the handset. It can be delivered with 1 to 3 buttons for autodialing of different numbers after lifting the handset.

### OPTIONS

- Auxiliary hook contact
- Call repeating relay for external repeaters
- Remote command relay on password DTMF
- Remote diagnostic software TelDia®

