

TELEINDUSTRIA srl

phone:+39 02 45713729 email:.....sales@teleindustria.it website: www.teleindustria.com

Emergency & Service VoIP SMART industrial telephone, shock-proof IK10 with auto fault-detection & audio test **TEL700T-Sip & TEL700TV-Sip**

ERCOTEL-ip™ (VOIP (SIP



















ORANGE

RAL2003



AVAILABLE COLO	, IV O	

YELLOW **GREY BLACK RED** RAL1023 RAL7030 RAL9005 RAL3020

Protection index [EN 60529]	IP66
Impact Resistance [EN 62262]	IK10
Operating temperature:	40°C ÷ +70°C
MTBF:	250.000 hours
MTTR:	3 minutes
Handset & Body materials:	aluminium + stainless steel
Colour of handset:	Grey, Black or Red
Hook:	magnetic
Handset's cord:	stainless-steel flexible, 200kg resistance
Bell:	95dB @ 1 m (with door closed or open)
	364 x 257 x 175 mm
Weight:	5,85 kg
-	

ORDER CODES

TEL700T-Sip:	Handset
TEL700TV-Sip:	Handset + Hands-Free

The ERCOTEL-ip® TEL700T/VoIP is probably the more performing and innovative Emergency & Hot-Line Telephone on the worldwide market. It is totally made of aluminum and INOX stainless-steel. The door is there to keep it clean, not for protecting against water and dust. In fact it is weather-proof IP66 & IK10 also when the door is open.

MAIN CHARACTERISTICS

Equipped with the native VoIP electronic card XCS-182 release 2022-1, HD Voice, DESQO™ ready. Protocol: SIP Power: PoE or 12Vdc SIP Servers:up to 3 SIP servers Electronic Bell: up to 95dB@1m, adjustable Hook: magnetic, high protection Programmable:webpage

The integrated electronic ringing bell 95dB at 1 meter is still operating without attenuation when the door is closed.

AFD - AUTOMATIC FAULT DETECTION

The telephone supports the automatic fault detection, including the audio test of microphone and earpiece. A Blue LED is permanently flashing to show the correct operability of the telephone. Ready for remote diagnostic software TelDia™.

The version TEL700TV/VoIP is equipped with handest + handsfree Full-Duplex facility. In this way the possible fault of the handset does not compromise the emergency functions.

- 14 keys keypad, with single aluminum buttons, with double function activated by the button Fn:
- 12 buttons (*, #, 0,1...9), R (flash), RP (last number redial)
- Pre-memorized call buttons (M1÷M8)
- Volume adjustment V+, V-
- Hook key, or hands-free mode (on TEL700TV/VoIP only)
- Door opening button, on DTMF password
- Red/Blue LED

- Auxiliary hook contact
- Call repeating relay for external repeaters
- Remote command relay on password DTMF Remote diagnostic software TelDia®

