

TELEINDUSTRIA srl


phone: +39 02 45713729

email: sales@teleindustria.it

website: www.teleindustria.com

Smart VoIP Hands-Free telephone watertight IP66 & shockproof IK10, recessed mounting, suitable for pillars Automatic Fault Detection & Remote Interrogation, model TEL249M1-Sip

STEELVOX-ip™



WIDE RANGE

STEEL-VOX® is available with 1, 2, 4, 8 buttons for pre-memorized numbers or with full telephone keypad.



Protection index : IP66 [EN 60529]
Impact Resistance : IK10 [EN 60068]
Max relative humidity [EN 60068-2-30]98%
Operating temperatures: -40°C ÷ +70°C
Material:stainless steel INOX
MTBF: >180.000 hours
MTTR: 3 minutes
Dimensions: 180x260x58 mm
Weight: 3,0 kg

STEELVOX-ip™ is a **SMART VoIP (SIP)** Full-Duplex hands-free telephone, made with a strong stainless steel plate (thickness 2mm) **vandal-resistant** and resistant to shocks **IK10**, with **IP66** protection. It comes with a metal frame for recessed mounting. The family **STEELVOX-ip™** is suitable to be installed in any pillar in our range. It ensures a **high quality of conversation** in industrial environments with **high ambient noise**.

STEELVOX-ip™ is vastly used both to carry out functions of **Service & SOS Emergency**. It supports up to **three relays** activated by **DTMF password**.

The model **TEL249M1-Sip** is equipped with a single red button for calling pre-stored numbers. The **STEELVOX-ip™** range includes numerous variants, including a version with extended metallic telephone 15 buttons keypad.

TEL249M1-VoIP with 1 Call Button

The **TEL249M1-Sip** is equipped with only one **red button** for the automatic dialling of one or more **pre-stored telephone numbers**. If properly programmed, the button can be used for manual answer to incoming calls. However, you can program your phone to automatically answer after a predetermined number of ring tones.

- Red LED indicating "on line" status
- Blue LED signalling good work conditions or fault

MAIN FEATURES

Equipped with the native VoIP electronic card XCS-182 release 2022-1, HD Voice, DESQO™ ready.

Protocol:SIP
Power: PoE or 12Vdc
SIP Servers:up to 3 SIP servers
Electronic Bell:up to 95dB@1m, adjustable
Hook: magnetic, high protection
Programmable: webpage

OPTIONS

- Auto Fault detection with audio local test
- Booster amplifier
- Auxiliary hook contact
- Up to 3 Relais activated on DTMF passwords
- Remote diagnostic interrogation by TelDia®
- Fault alarm relay (FAR-01) at 12Vdc

AFD - Automatic Fault-Detection

The telephone can be equipped with the optional function of "fault detection", so that all the parameters of the telephone are periodically tasted, including the audio-test of microphone and loudspeaker. A Blue LED is flashing to show that the telephone is in good working conditions. The status of the telephone can be remotely interrogated by the specialized software TelDia®.

ORDER CODES

TEL249M1- Sip 1 button
TEL249M2- Sip 2 buttons
TEL249M4- Sip 4 buttons
TEL249M8- Sip 8 buttons
TEL249T- Sip full telephone keypad