

TELEINDUSTRIA srl

Phone:(39) 2 45713729

Fax:(39) 2 45714000

E-mail: sales@teleindustria.it

Web-site: www.teleindustria.com

Smart VoIP Hands-Free telephone watertight IP66 & shockproof IK10, recessed mounting, suitable for pillars Automatic Fault Detection & Remote Interrogation, model TEL249M2-VoIP

STEELVOX-ip®



WIDE RANGE OF VERSIONS

STEEL-VOX® is available with 1, 2, 4, 8 buttons for pre-memorized numbers or with full telephone keypad.



Protection index : IP66 [EN 60529]
Impact Resistance : IK10 [EN 60068]
Max relative humidity [EN 60068-2-30]98%
Operating temperatures:-40°C ÷ +70°C
Material:stainless steel INOX
MTBF: >180.000 hours
MTTR: 3 minutes
Dimensions: 180x260x58 mm
Weight: 3,0 kg

STEELVOX-ip® is a **SMART VoIP (SIP)** Full-Duplex hands-free telephone, made with a strong stainless steel plate (2 mm) **vandal-resistant** and resistant to shocks **IK10**, with **IP66** protection. It comes with a metal frame for recessed mounting. The family **STEELVOX-ip®** is suitable to be installed in any pillar in our range. It ensures a **high quality of conversation** in industrial environments with **high ambient noise**.

STEELVOX-ip® is vastly used both to carry out functions of **Service & SOS Emergency**. It supports up to **three relays** activated by **DTMF password**.

The model **TEL249M2-VoIP** is equipped with two red buttons for calling pre-stored numbers. The **STEELVOX-ip®** range includes numerous variants, including a version with extended metallic telephone 15 buttons keypad.

TEL249M1-VoIP with 2 Call Buttons

The **TEL249M2-VoIP** is equipped with two **red buttons** for the automatic dialling of one or more **pre-stored telephone numbers**. If properly programmed, the button can be used for manual answer to incoming calls. However, you can program your phone to automatically answer after a predetermined number of ring tones.

- Red LED indicating "on line" status
- Blue LED signalling good work conditions or fault

Main Characteristics

VoIP SIP protocol, DHCP addressing
Power supply: 12 Vdc or POE
Electronic Bell: 85dB at 1 m
Autoreply: programmable, 1÷90 rings
Hang-up: automatic at the end of conversation
Programmable:100% remotely programmable

Additional functions (options)

- Auto Fault detection with audio local test
- Booster amplifier
- Auxiliary hook contact
- Up to 3 Relais activated on DTMF passwords
- Remote diagnostic interrogation by TelDia®
- Fault alarm relay (FAR-01) at 12Vdc

Automatic Fault-Detection function:

The telephone can be equipped with the optional function of "fault detection", so that all the parameters of the telephone are periodically tasted, including the audio-test of microphone and loudspeaker. A Blue LED is flashing to show that the telephone is in good working conditions. The status of the telephone can be remotely interrogated by the specialized software TelDia®.

ORDER CODES

TEL249M1-VoIP..... 1 button
TEL249M2-VoIP.....2 buttons
TEL249M4-VoIP.....4 buttons
TEL249M8-VoIP.....8 buttons
TEL249T-VoIP full telephone keypad